

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): AQS 25					试验条件(Condition): 空气气氛下保温 1 小时				
适用温度范围(Temperature): 650 °C ~ 1000 °C					允许误差范围(Deviation): ± 1 °C ~ 3 °C				
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
19.43	650	18.98	684	18.53	761	18.08	816	17.63	861
19.42	651	18.97	685	18.52	763	18.07	817	17.62	862
19.41	651	18.96	686	18.51	764	18.06	818	17.61	863
19.40	652	18.95	687	18.50	766	18.05	820	17.60	864
19.39	652	18.94	688	18.49	767	18.04	821	17.59	865
19.38	653	18.93	690	18.48	769	18.03	822	17.58	866
19.37	653	18.92	691	18.47	770	18.02	823	17.57	867
19.36	654	18.91	693	18.46	772	18.01	824	17.56	868
19.35	654	18.90	695	18.45	773	18.00	825	17.55	869
19.34	655	18.89	696	18.44	774	17.99	826	17.54	870
19.33	656	18.88	698	18.43	776	17.98	827	17.53	871
19.32	656	18.87	700	18.42	777	17.97	828	17.52	872
19.31	657	18.86	702	18.41	778	17.96	829	17.51	874
19.30	657	18.85	703	18.40	780	17.95	830	17.50	875
19.29	658	18.84	705	18.39	781	17.94	830	17.49	876
19.28	658	18.83	707	18.38	782	17.93	831	17.48	877
19.27	659	18.82	709	18.37	783	17.92	832	17.47	878
19.26	660	18.81	711	18.36	785	17.91	833	17.46	879
19.25	660	18.80	713	18.35	786	17.90	834	17.45	880
19.24	661	18.79	715	18.34	787	17.89	835	17.44	881
19.23	661	18.78	717	18.33	788	17.88	836	17.43	882
19.22	662	18.77	719	18.32	789	17.87	837	17.42	883
19.21	663	18.76	721	18.31	791	17.86	838	17.41	885
19.20	663	18.75	724	18.30	792	17.85	839	17.40	886
19.19	664	18.74	726	18.29	793	17.84	840	17.39	887
19.18	665	18.73	728	18.28	794	17.83	841	17.38	888
19.17	666	18.72	730	18.27	795	17.82	842	17.37	889
19.16	666	18.71	731	18.26	797	17.81	843	17.36	890
19.15	667	18.70	733	18.25	798	17.80	844	17.35	892
19.14	668	18.69	735	18.24	799	17.79	845	17.34	893
19.13	669	18.68	737	18.23	800	17.78	846	17.33	894
19.12	670	18.67	739	18.22	801	17.77	847	17.32	895
19.11	670	18.66	741	18.21	802	17.76	848	17.31	896
19.10	671	18.65	743	18.20	803	17.75	849	17.30	898
19.09	672	18.64	745	18.19	804	17.74	850	17.29	899
19.08	673	18.63	746	18.18	806	17.73	851	17.28	900
19.07	674	18.62	748	18.17	807	17.72	852	17.27	902
19.06	675	18.61	750	18.16	808	17.71	853	17.26	903
19.05	676	18.60	751	18.15	809	17.70	854	17.25	904
19.04	677	18.59	753	18.14	810	17.69	855	17.24	905
19.03	678	18.58	755	18.13	811	17.68	856	17.23	906
19.02	679	18.57	756	18.12	812	17.67	857	17.22	907
19.01	680	18.56	757	18.11	813	17.66	858	17.21	909
19.00	681	18.55	759	18.10	814	17.65	859	17.20	910
18.99	683	18.54	760	18.09	815	17.64	860	17.19	912
产品规格: Φ ₀ 20 × Φ _i 10 × h 7mm, 绿色 (Green)					检验工程师 (Inspector):				
生产批号 (Batch No.): AQS 25					生产日期 (Date): 2013-01-22				

ISO 9001:2000

