

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

| 生产批号 (Batch No.): BQS 17 | | | | 试验条件(Condition): 空气气氛下保温 1 小时 | | | |
|---|----------------|-----------------|----------------|---|----------------|-----------------|----------------|
| 适用温度范围(Temperature): 900 °C ~ 1200 °C | | | | 允许误差范围(Deviation): ± 1 °C ~ 3 °C | | | |
| 校温环外径 Φ (mm) | 烧成温度 T (°C) | 校温环外径 Φ (mm) | 烧成温度 T (°C) | 校温环外径 Φ (mm) | 烧成温度 T (°C) | 校温环外径 Φ (mm) | 烧成温度 T (°C) |
| | | 18.78 | 971 | 18.28 | 1069 | 17.78 | 1137 |
| | | 18.77 | 973 | 18.27 | 1070 | 17.77 | 1138 |
| | | 18.76 | 975 | 18.26 | 1072 | 17.76 | 1140 |
| | | 18.75 | 976 | 18.25 | 1073 | 17.75 | 1141 |
| | | 18.74 | 978 | 18.24 | 1075 | 17.74 | 1143 |
| 19.23 | 890 | 18.73 | 980 | 18.23 | 1076 | 17.73 | 1144 |
| 19.22 | 892 | 18.72 | 982 | 18.22 | 1078 | 17.72 | 1146 |
| 19.21 | 894 | 18.71 | 984 | 18.21 | 1079 | 17.71 | 1148 |
| 19.20 | 897 | 18.70 | 986 | 18.20 | 1081 | 17.70 | 1149 |
| 19.19 | 900 | 18.69 | 988 | 18.19 | 1082 | 17.69 | 1151 |
| 19.18 | 902 | 18.68 | 990 | 18.18 | 1084 | 17.68 | 1153 |
| 19.17 | 904 | 18.67 | 992 | 18.17 | 1085 | 17.67 | 1155 |
| 19.16 | 907 | 18.66 | 994 | 18.16 | 1086 | 17.66 | 1156 |
| 19.15 | 909 | 18.65 | 996 | 18.15 | 1088 | 17.65 | 1158 |
| 19.14 | 911 | 18.64 | 998 | 18.14 | 1089 | 17.64 | 1160 |
| 19.13 | 913 | 18.63 | 1000 | 18.13 | 1091 | 17.63 | 1163 |
| 19.12 | 914 | 18.62 | 1002 | 18.12 | 1092 | 17.62 | 1165 |
| 19.11 | 916 | 18.61 | 1004 | 18.11 | 1093 | 17.61 | 1167 |
| 19.10 | 918 | 18.60 | 1006 | 18.10 | 1095 | 17.60 | 1170 |
| 19.09 | 919 | 18.59 | 1008 | 18.09 | 1096 | 17.59 | 1172 |
| 19.08 | 921 | 18.58 | 1010 | 18.08 | 1097 | 17.58 | 1175 |
| 19.07 | 923 | 18.57 | 1013 | 18.07 | 1099 | 17.57 | 1178 |
| 19.06 | 925 | 18.56 | 1015 | 18.06 | 1100 | 17.56 | 1181 |
| 19.05 | 926 | 18.55 | 1017 | 18.05 | 1101 | 17.55 | 1185 |
| 19.04 | 928 | 18.54 | 1019 | 18.04 | 1103 | 17.54 | 1189 |
| 19.03 | 930 | 18.53 | 1021 | 18.03 | 1104 | 17.53 | 1193 |
| 19.02 | 931 | 18.52 | 1024 | 18.02 | 1105 | 17.52 | 1197 |
| 19.01 | 933 | 18.51 | 1026 | 18.01 | 1106 | 17.51 | 1200 |
| 19.00 | 935 | 18.50 | 1028 | 18.00 | 1108 | 17.50 | 1203 |
| 18.99 | 936 | 18.49 | 1030 | 17.99 | 1109 | 17.49 | 1206 |
| 18.98 | 938 | 18.48 | 1032 | 17.98 | 1110 | 17.48 | 1209 |
| 18.97 | 940 | 18.47 | 1034 | 17.97 | 1112 | 17.47 | 1211 |
| 18.96 | 941 | 18.46 | 1036 | 17.96 | 1113 | 17.46 | 1213 |
| 18.95 | 943 | 18.45 | 1038 | 17.95 | 1114 | 17.45 | 1215 |
| 18.94 | 945 | 18.44 | 1040 | 17.94 | 1116 | 17.44 | 1216 |
| 18.93 | 946 | 18.43 | 1042 | 17.93 | 1117 | 17.43 | 1218 |
| 18.92 | 948 | 18.42 | 1044 | 17.92 | 1118 | 17.42 | 1219 |
| 18.91 | 949 | 18.41 | 1046 | 17.91 | 1119 | 17.41 | 1220 |
| 18.90 | 951 | 18.40 | 1047 | 17.90 | 1121 | 17.40 | 1221 |
| 18.89 | 953 | 18.39 | 1049 | 17.89 | 1122 | 17.39 | 1222 |
| 18.88 | 954 | 18.38 | 1051 | 17.88 | 1123 | 17.38 | 1223 |
| 18.87 | 956 | 18.37 | 1053 | 17.87 | 1125 | 17.37 | 1224 |
| 18.86 | 958 | 18.36 | 1055 | 17.86 | 1126 | 17.36 | 1225 |
| 18.85 | 959 | 18.35 | 1057 | 17.85 | 1127 | 17.35 | 1226 |
| 18.84 | 961 | 18.34 | 1058 | 17.84 | 1129 | 17.34 | 1227 |
| 18.83 | 963 | 18.33 | 1060 | 17.83 | 1130 | | |
| 18.82 | 964 | 18.32 | 1062 | 17.82 | 1131 | | |
| 18.81 | 966 | 18.31 | 1064 | 17.81 | 1133 | | |
| 18.80 | 968 | 18.30 | 1065 | 17.80 | 1134 | | |
| 18.79 | 969 | 18.29 | 1067 | 17.79 | 1136 | | |
| 产品规格: Φ _o 20 × Φ _i 10 × h 7mm, 红色 (Red) | | | | 检验工程师 (Inspector): 黄满连 | | | |
| 生产批号 (Batch No.): BQS 17 | | | | 生产日期 (Date): 2006 年 11 月 15 日 | | | |

ISO 9001:2000

