

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): BQS 24				试验条件(Condition): 空气气氛下保温 1 小时			
适用温度范围(Temperature): 900 °C ~ 1200 °C				允许误差范围(Deviation): ± 1 °C ~ 3 °C			
校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)
19.12	899	18.77	975	18.42	1045	18.07	1105
19.11	901	18.76	979	18.41	1047	18.06	1107
19.10	903	18.75	982	18.40	1048	18.05	1109
19.09	905	18.74	985	18.39	1050	18.04	1111
19.08	907	18.73	989	18.38	1052	18.03	1114
19.07	909	18.72	992	18.37	1053	18.02	1117
19.06	910	18.71	994	18.36	1054	18.01	1119
19.05	912	18.70	997	18.35	1056	18.00	1122
19.04	913	18.69	999	18.34	1058	17.99	1124
19.03	915	18.68	1001	18.33	1059	17.98	1127
19.02	916	18.67	1004	18.32	1061	17.97	1130
19.01	918	18.66	1006	18.31	1062	17.96	1133
19.00	919	18.65	1008	18.30	1063	17.95	1136
18.99	920	18.64	1010	18.29	1064	17.94	1139
18.98	921	18.63	1012	18.28	1066	17.93	1142
18.97	923	18.62	1014	18.27	1068	17.92	1145
18.96	924	18.61	1016	18.26	1069	17.91	1148
18.95	926	18.60	1018	18.25	1071	17.90	1152
18.94	928	18.59	1020	18.24	1073	17.89	1155
18.93	930	18.58	1021	18.23	1074	17.88	1159
18.92	931	18.57	1022	18.22	1076	17.87	1162
18.91	933	18.56	1024	18.21	1078	17.86	1165
18.90	935	18.55	1026	18.20	1080	17.85	1169
18.89	937	18.54	1027	18.19	1081	17.84	1173
18.88	939	18.53	1029	18.18	1082	17.83	1177
18.87	941	18.52	1031	18.17	1084	17.82	1181
18.86	944	18.51	1032	18.16	1086	17.81	1184
18.85	946	18.50	1034	18.15	1088	17.80	1188
18.84	949	18.49	1035	18.14	1090	17.79	1192
18.83	952	18.48	1037	18.13	1092	17.78	1196
18.82	956	18.47	1039	18.12	1094		
18.81	959	18.46	1040	18.11	1096	17.77	1199
18.80	963	18.45	1041	18.10	1098	17.76	1201
18.79	967	18.44	1042	18.09	1101		
18.78	971	18.43	1044	18.08	1103		

产品规格: $\Phi_0 20 \times \Phi_1 10 \times h 3.5\text{mm}$, 红色 (Red) | 检验工程师 (Inspector):

生产批号 (Batch No.): **BQS 24** | 生产日期 (Date): 2011-05-26

ISO 9001:2000

