

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): CQS 42				试验条件(Condition): 空气气氛下保温 1 小时					
适用温度范围(Temperature): 1100 °C ~ 1400 °C				允许误差范围(Deviation): ± 1 °C ~ 3 °C					
校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)
		19.33	1183	18.78	1244	18.23	1297	17.68	1343
		19.32	1184	18.77	1246	18.22	1298	17.67	1344
		19.31	1185	18.76	1247	18.21	1299	17.66	1345
		19.30	1187	18.75	1248	18.20	1300	17.65	1346
		19.29	1188	18.74	1249	18.19	1301	17.64	1347
19.83	1098	19.28	1189	18.73	1250	18.18	1302	17.63	1348
19.82	1101	19.27	1190	18.72	1251	18.17	1302	17.62	1349
19.81	1104	19.26	1191	18.71	1252	18.16	1303	17.61	1350
19.80	1107	19.25	1193	18.70	1252	18.15	1304	17.60	1351
19.79	1109	19.24	1194	18.69	1253	18.14	1305	17.59	1352
19.78	1112	19.23	1195	18.68	1254	18.13	1306	17.58	1353
19.77	1114	19.22	1196	18.67	1255	18.12	1307	17.57	1354
19.76	1116	19.21	1197	18.66	1256	18.11	1308	17.56	1355
19.75	1119	19.20	1199	18.65	1257	18.10	1308	17.55	1356
19.74	1121	19.19	1200	18.64	1258	18.09	1309	17.54	1357
19.73	1123	19.18	1201	18.63	1259	18.08	1310	17.53	1358
19.72	1125	19.17	1202	18.62	1260	18.07	1311	17.52	1359
19.71	1127	19.16	1203	18.61	1262	18.06	1312	17.51	1360
19.70	1129	19.15	1204	18.60	1263	18.05	1313	17.50	1361
19.69	1130	19.14	1205	18.59	1264	18.04	1314	17.49	1362
19.68	1132	19.13	1207	18.58	1265	18.03	1314	17.48	1363
19.67	1134	19.12	1208	18.57	1266	18.02	1315	17.47	1364
19.66	1136	19.11	1209	18.56	1267	18.01	1316	17.46	1365
19.65	1138	19.10	1210	18.55	1268	18.00	1317	17.45	1366
19.64	1139	19.09	1211	18.54	1269	17.99	1318	17.44	1367
19.63	1140	19.08	1212	18.53	1270	17.98	1319	17.43	1369
19.62	1142	19.07	1213	18.52	1271	17.97	1319	17.42	1370
19.61	1144	19.06	1214	18.51	1272	17.96	1320	17.41	1371
19.60	1145	19.05	1215	18.50	1273	17.95	1321	17.40	1373
19.59	1147	19.04	1216	18.49	1274	17.94	1322	17.39	1374
19.58	1149	19.03	1217	18.48	1275	17.93	1323	17.38	1376
19.57	1150	19.02	1218	18.47	1276	17.92	1324	17.37	1377
19.56	1152	19.01	1219	18.46	1277	17.91	1324	17.36	1379
19.55	1153	19.00	1220	18.45	1278	17.90	1325	17.35	1380
19.54	1155	18.99	1221	18.44	1279	17.89	1326	17.34	1382
19.53	1156	18.98	1223	18.43	1280	17.88	1327	17.33	1383
19.52	1158	18.97	1224	18.42	1281	17.87	1328	17.32	1385
19.51	1159	18.96	1225	18.41	1282	17.86	1328	17.31	1386
19.50	1161	18.95	1226	18.40	1283	17.85	1329	17.30	1388
19.49	1162	18.94	1227	18.39	1283	17.84	1329	17.29	1389
19.48	1164	18.93	1228	18.38	1284	17.83	1330	17.28	1391
19.47	1165	18.92	1229	18.37	1285	17.82	1331	17.27	1392
19.46	1167	18.91	1230	18.36	1286	17.81	1332	17.26	1394
19.45	1168	18.90	1231	18.35	1287	17.80	1333	17.25	1395
19.44	1169	18.89	1232	18.34	1288	17.79	1334	17.24	1396
19.43	1171	18.88	1234	18.33	1289	17.78	1334		
19.42	1172	18.87	1235	18.32	1290	17.77	1335	17.23	1398
19.41	1173	18.86	1236	18.31	1290	17.76	1336	17.22	1399
19.40	1175	18.85	1237	18.30	1291	17.75	1337	17.21	1400
19.39	1176	18.84	1238	18.29	1292	17.74	1338		
19.38	1177	18.83	1239	18.28	1293	17.73	1339		
19.37	1178	18.82	1240	18.27	1294	17.72	1340		
19.36	1179	18.81	1241	18.26	1294	17.71	1341		
19.35	1180	18.80	1242	18.25	1295	17.70	1341		
19.34	1182	18.79	1243	18.24	1296	17.69	1342		
产品规格: Φ ₀ 20 × Φ ₁ 10 × h 7mm, 兰色 (Blue)				检验工程师 (Inspector): 黄满连					
生产批号 (Batch No.): CQS 42				生产日期 (Date): 2010-05-10					

ISO 9001:2000

