

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): CQS 46				试验条件(Condition): 空气气氛下保温 1 小时							
适用温度范围(Temperature): 1100 °C ~ 1400 °C				允许误差范围(Deviation): ± 1 °C ~ 3 °C							
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)		
19.70	1099	19.15	1156	18.60	1196	18.05	1235	17.50	1276	16.95	1326
19.69	1101	19.14	1157	18.59	1197	18.04	1236	17.49	1277	16.94	1327
19.68	1103	19.13	1158	18.58	1197	18.03	1237	17.48	1277	16.93	1328
19.67	1105	19.12	1158	18.57	1198	18.02	1237	17.47	1278	16.92	1330
19.66	1107	19.11	1159	18.56	1199	18.01	1238	17.46	1279	16.91	1331
19.65	1109	19.10	1160	18.55	1199	18.00	1239	17.45	1280	16.90	1332
19.64	1111	19.09	1161	18.54	1200	17.99	1240	17.44	1281	16.89	1333
19.63	1112	19.08	1161	18.53	1201	17.98	1240	17.43	1282	16.88	1334
19.62	1114	19.07	1162	18.52	1202	17.97	1241	17.42	1282	16.87	1335
19.61	1115	19.06	1163	18.51	1202	17.96	1242	17.41	1283	16.86	1336
19.60	1116	19.05	1163	18.50	1203	17.95	1243	17.40	1284	16.85	1337
19.59	1118	19.04	1164	18.49	1204	17.94	1243	17.39	1285	16.84	1338
19.58	1119	19.03	1165	18.48	1205	17.93	1244	17.38	1286	16.83	1339
19.57	1120	19.02	1166	18.47	1205	17.92	1245	17.37	1286	16.82	1341
19.56	1121	19.01	1166	18.46	1206	17.91	1246	17.36	1287	16.81	1342
19.55	1123	19.00	1167	18.45	1207	17.90	1246	17.35	1288	16.80	1343
19.54	1124	18.99	1168	18.44	1207	17.89	1247	17.34	1289	16.79	1344
19.53	1125	18.98	1169	18.43	1208	17.88	1248	17.33	1290	16.78	1346
19.52	1126	18.97	1169	18.42	1209	17.87	1249	17.32	1291	16.77	1347
19.51	1127	18.96	1170	18.41	1210	17.86	1249	17.31	1291	16.76	1348
19.50	1128	18.95	1171	18.40	1210	17.85	1250	17.30	1292	16.75	1350
19.49	1129	18.94	1171	18.39	1211	17.84	1251	17.29	1293	16.74	1351
19.48	1130	18.93	1172	18.38	1212	17.83	1252	17.28	1294	16.73	1352
19.47	1131	18.92	1173	18.37	1212	17.82	1252	17.27	1295	16.72	1354
19.46	1132	18.91	1174	18.36	1213	17.81	1253	17.26	1296	16.71	1355
19.45	1133	18.90	1174	18.35	1213	17.80	1254	17.25	1297	16.70	1357
19.44	1134	18.89	1175	18.34	1214	17.79	1255	17.24	1298	16.69	1358
19.43	1135	18.88	1176	18.33	1215	17.78	1255	17.23	1298	16.68	1359
19.42	1135	18.87	1176	18.32	1215	17.77	1256	17.22	1299	16.67	1361
19.41	1136	18.86	1177	18.31	1216	17.76	1257	17.21	1300	16.66	1362
19.40	1137	18.85	1178	18.30	1217	17.75	1258	17.20	1301	16.65	1364
19.39	1138	18.84	1179	18.29	1217	17.74	1258	17.19	1302	16.64	1365
19.38	1139	18.83	1179	18.28	1218	17.73	1259	17.18	1303	16.63	1367
19.37	1140	18.82	1180	18.27	1219	17.72	1260	17.17	1304	16.62	1368
19.36	1141	18.81	1181	18.26	1220	17.71	1261	17.16	1305	16.61	1370
19.35	1141	18.80	1181	18.25	1220	17.70	1261	17.15	1306	16.60	1371
19.34	1142	18.79	1182	18.24	1221	17.69	1262	17.14	1307	16.59	1373
19.33	1143	18.78	1183	18.23	1222	17.68	1263	17.13	1308	16.58	1374
19.32	1144	18.77	1184	18.22	1223	17.67	1264	17.12	1309	16.57	1376
19.31	1145	18.76	1184	18.21	1223	17.66	1264	17.11	1310	16.56	1378
19.30	1146	18.75	1185	18.20	1224	17.65	1265	17.10	1311	16.55	1379
19.29	1146	18.74	1186	18.19	1225	17.64	1266	17.09	1311	16.54	1381
19.28	1147	18.73	1186	18.18	1226	17.63	1267	17.08	1312	16.53	1383
19.27	1148	18.72	1187	18.17	1226	17.62	1268	17.07	1313	16.52	1385
19.26	1149	18.71	1188	18.16	1227	17.61	1268	17.06	1314	16.51	1387
19.25	1150	18.70	1189	18.15	1228	17.60	1269	17.05	1315	16.50	1389
19.24	1150	18.69	1189	18.14	1228	17.59	1270	17.04	1317	16.49	1392
19.23	1151	18.68	1190	18.13	1229	17.58	1271	17.03	1318	16.48	1395
19.22	1152	18.67	1191	18.12	1230	17.57	1271	17.02	1319	16.47	1398
19.21	1152	18.66	1191	18.11	1231	17.56	1272	17.01	1320	16.46	1400
19.20	1153	18.65	1192	18.10	1231	17.55	1273	17.00	1321		
19.19	1154	18.64	1193	18.09	1232	17.54	1273	16.99	1322		
19.18	1154	18.63	1194	18.08	1233	17.53	1274	16.98	1323		
19.17	1155	18.62	1194	18.07	1234	17.52	1274	16.97	1324		
19.16	1155	18.61	1195	18.06	1234	17.51	1275	16.96	1325		

产品规格: $\Phi_o 20 \times \Phi_i 10 \times h 7mm$, 兰色 (Blue)	检验工程师 (Inspector): 黄满连
生产批号 (Batch No.): CQS 46	生产日期 (Date): 2010-12-10

ISO 9001:2000

