

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): CQS 49				试验条件(Condition): 空气气氛下保温 1 小时							
适用温度范围(Temperature): 1100 °C ~ 1400 °C				允许误差范围(Deviation): ± 1 °C ~ 3 °C							
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)				
		19.43	1169	18.88	1214	18.33	1255	17.78	1294	17.23	1335
		19.42	1170	18.87	1215	18.32	1256	17.77	1295	17.22	1336
		19.41	1171	18.86	1215	18.31	1256	17.76	1295	17.21	1337
		19.40	1172	18.85	1216	18.30	1257	17.75	1296	17.20	1338
		19.39	1173	18.84	1217	18.29	1258	17.74	1297	17.19	1338
		19.38	1174	18.83	1218	18.28	1259	17.73	1297	17.18	1339
		19.37	1175	18.82	1218	18.27	1259	17.72	1298	17.17	1340
		19.36	1176	18.81	1219	18.26	1260	17.71	1299	17.16	1341
		19.35	1176	18.80	1220	18.25	1261	17.70	1300	17.15	1342
		19.34	1177	18.79	1221	18.24	1262	17.69	1300	17.14	1343
19.88	1099	19.33	1178	18.78	1222	18.23	1262	17.68	1301	17.13	1344
19.87	1102	19.32	1179	18.77	1222	18.22	1263	17.67	1302	17.12	1345
19.86	1105	19.31	1179	18.76	1223	18.21	1264	17.66	1303	17.11	1346
19.85	1108	19.30	1180	18.75	1224	18.20	1265	17.65	1303	17.10	1347
19.84	1111	19.29	1181	18.74	1225	18.19	1265	17.64	1304	17.09	1348
19.83	1114	19.28	1182	18.73	1226	18.18	1266	17.63	1305	17.08	1350
19.82	1117	19.27	1183	18.72	1226	18.17	1267	17.62	1306	17.07	1351
19.81	1119	19.26	1184	18.71	1227	18.16	1268	17.61	1306	17.06	1352
19.80	1122	19.25	1185	18.70	1228	18.15	1268	17.60	1307	17.05	1353
19.79	1124	19.24	1186	18.69	1229	18.14	1269	17.59	1308	17.04	1354
19.78	1126	19.23	1186	18.68	1229	18.13	1270	17.58	1309	17.03	1355
19.77	1128	19.22	1187	18.67	1230	18.12	1271	17.57	1309	17.02	1356
19.76	1130	19.21	1188	18.66	1231	18.11	1271	17.56	1310	17.01	1357
19.75	1132	19.20	1189	18.65	1232	18.10	1272	17.55	1311	17.00	1358
19.74	1134	19.19	1190	18.64	1233	18.09	1273	17.54	1312	16.99	1359
19.73	1135	19.18	1191	18.63	1233	18.08	1273	17.53	1312	16.98	1361
19.72	1136	19.17	1192	18.62	1234	18.07	1274	17.52	1313	16.97	1362
19.71	1138	19.16	1192	18.61	1235	18.06	1275	17.51	1314	16.96	1364
19.70	1139	19.15	1193	18.60	1235	18.05	1275	17.50	1314	16.95	1365
19.69	1141	19.14	1194	18.59	1236	18.04	1276	17.49	1315	16.94	1367
19.68	1142	19.13	1195	18.58	1236	18.03	1276	17.48	1315	16.93	1369
19.67	1144	19.12	1195	18.57	1237	18.02	1277	17.47	1316	16.92	1370
19.66	1145	19.11	1196	18.56	1238	18.01	1278	17.46	1317	16.91	1372
19.65	1146	19.10	1197	18.55	1239	18.00	1279	17.45	1318	16.90	1373
19.64	1147	19.09	1197	18.54	1239	17.99	1279	17.44	1318	16.89	1375
19.63	1149	19.08	1198	18.53	1240	17.98	1280	17.43	1319	16.88	1377
19.62	1150	19.07	1199	18.52	1241	17.97	1281	17.42	1320	16.87	1380
19.61	1151	19.06	1200	18.51	1242	17.96	1282	17.41	1321	16.86	1382
19.60	1152	19.05	1201	18.50	1243	17.95	1282	17.40	1322	16.85	1385
19.59	1153	19.04	1201	18.49	1243	17.94	1283	17.39	1322	16.84	1387
19.58	1154	19.03	1202	18.48	1244	17.93	1284	17.38	1323	16.83	1390
19.57	1155	19.02	1203	18.47	1245	17.92	1284	17.37	1324	16.82	1393
19.56	1156	19.01	1204	18.46	1246	17.91	1285	17.36	1325	16.81	1395
19.55	1157	19.00	1205	18.45	1246	17.90	1286	17.35	1326	16.80	1398
19.54	1158	18.99	1206	18.44	1247	17.89	1287	17.34	1326	16.79	1401
19.53	1159	18.98	1206	18.43	1248	17.88	1287	17.33	1327		
19.52	1160	18.97	1207	18.42	1249	17.87	1288	17.32	1328		
19.51	1161	18.96	1208	18.41	1250	17.86	1289	17.31	1329		
19.50	1162	18.95	1209	18.40	1250	17.85	1290	17.30	1330		
19.49	1163	18.94	1210	18.39	1251	17.84	1290	17.29	1331		
19.48	1164	18.93	1210	18.38	1252	17.83	1291	17.28	1331		
19.47	1165	18.92	1211	18.37	1253	17.82	1292	17.27	1332		
19.46	1166	18.91	1212	18.36	1253	17.81	1292	17.26	1333		
19.45	1167	18.90	1213	18.35	1254	17.80	1293	17.25	1334		
19.44	1168	18.89	1214	18.34	1255	17.79	1294	17.24	1334		

产品规格: Φ₀20 × Φ₁10 × h 7mm, 兰色 (Blue) 检验工程师 (Inspector): 黄满连

生产批号 (Batch No.): **CQS 49** 生产日期 (Date): 2011-07-21

ISO 9001:2000

