

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type): AQS 14				试验条件(Condition): 空气气氛下保温 1 小时					
适用温度范围(Temperature): 650 °C ~ 1000 °C				允许误差范围(Deviation): ± 1 °C ~ 3 °C					
校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)	校温环外径 Φ (mm)	烧成温度 T (°C)
19.41	648	18.96	752	18.51	835	18.06	895	17.61	956
19.40	651	18.95	754	18.50	836	18.05	896	17.60	957
19.39	654	18.94	757	18.49	838	18.04	897	17.59	958
19.38	657	18.93	759	18.48	839	18.03	899	17.58	960
19.37	660	18.92	761	18.47	840	18.02	900	17.57	961
19.36	663	18.91	763	18.46	842	18.01	902	17.56	962
19.35	666	18.90	765	18.45	843	18.00	904	17.55	963
19.34	669	18.89	768	18.44	844	17.99	905	17.54	964
19.33	672	18.88	771	18.43	846	17.98	906	17.53	965
19.32	675	18.87	773	18.42	847	17.97	908	17.52	966
19.31	677	18.86	775	18.41	848	17.96	909	17.51	967
19.30	679	18.85	777	18.40	850	17.95	910	17.50	968
19.29	681	18.84	779	18.39	852	17.94	912	17.49	969
19.28	684	18.83	781	18.38	853	17.93	913	17.48	970
19.27	686	18.82	783	18.37	854	17.92	915	17.47	971
19.26	688	18.81	785	18.36	856	17.91	916	17.46	972
19.25	691	18.80	787	18.35	857	17.90	917	17.45	973
19.24	693	18.79	789	18.34	858	17.89	919	17.44	974
19.23	695	18.78	791	18.33	859	17.88	920	17.43	975
19.22	697	18.77	793	18.32	861	17.87	921	17.42	976
19.21	699	18.76	795	18.31	862	17.86	923	17.41	977
19.20	701	18.75	797	18.30	863	17.85	924	17.40	978
19.19	703	18.74	799	18.29	864	17.84	925	17.39	979
19.18	705	18.73	801	18.28	866	17.83	927	17.38	980
19.17	707	18.72	803	18.27	867	17.82	929	17.37	981
19.16	709	18.71	804	18.26	868	17.81	931	17.36	983
19.15	711	18.70	806	18.25	869	17.80	932	17.35	984
19.14	713	18.69	808	18.24	871	17.79	933	17.34	985
19.13	715	18.68	809	18.23	872	17.78	934	17.33	986
19.12	718	18.67	811	18.22	873	17.77	936	17.32	987
19.11	720	18.66	812	18.21	875	17.76	937	17.31	988
19.10	722	18.65	814	18.20	877	17.75	938	17.30	989
19.09	724	18.64	815	18.19	878	17.74	940	17.29	990
19.08	726	18.63	817	18.18	879	17.73	941	17.28	991
19.07	728	18.62	818	18.17	880	17.72	942	17.27	992
19.06	730	18.61	820	18.16	882	17.71	943	17.26	993
19.05	732	18.60	822	18.15	883	17.70	945	17.25	994
19.04	734	18.59	824	18.14	884	17.69	946	17.24	995
19.03	736	18.58	825	18.13	886	17.68	947	17.23	996
19.02	738	18.57	827	18.12	887	17.67	948	17.22	997
19.01	741	18.56	828	18.11	888	17.66	949		
19.00	744	18.55	830	18.10	889	17.65	951	17.21	999
18.99	746	18.54	831	18.09	891	17.64	952	17.20	1000
18.98	748	18.53	832	18.08	892	17.63	953		
18.97	750	18.52	834	18.07	893	17.62	954		
产品规格: Φ ₀ 20 × Φ ₁ 10 × h 7mm, 绿色 (Green)				检验工程师 (Inspector): 黄满连					
生产批号 (Batch No.): AQS 14				生产日期 (Date): 2010-03-16					

ISO 9001:2000

