

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type):		AQS 19		试验条件(Condition):		空气气氛下保温 1 小时			
适用温度范围(Temperature):		650 °C ~ 1000 °C		允许误差范围(Deviation):		± 1 °C ~ 3 °C			
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
19.47	650	18.97	734	18.47	808	17.97	859	17.47	909
19.46	651	18.96	736	18.46	809	17.96	860	17.46	910
19.45	653	18.95	738	18.45	810	17.95	861	17.45	911
19.44	654	18.94	740	18.44	812	17.94	862	17.44	912
19.43	655	18.93	742	18.43	813	17.93	863	17.43	913
19.42	656	18.92	743	18.42	814	17.92	864	17.42	915
19.41	658	18.91	745	18.41	815	17.91	865	17.41	916
19.40	659	18.90	747	18.40	816	17.90	866	17.40	917
19.39	660	18.89	749	18.39	817	17.89	867	17.39	918
19.38	661	18.88	751	18.38	818	17.88	867	17.38	919
19.37	663	18.87	752	18.37	819	17.87	868	17.37	921
19.36	664	18.86	754	18.36	820	17.86	869	17.36	922
19.35	665	18.85	756	18.35	821	17.85	870	17.35	923
19.34	667	18.84	757	18.34	822	17.84	871	17.34	924
19.33	668	18.83	759	18.33	823	17.83	872	17.33	926
19.32	670	18.82	761	18.32	824	17.82	873	17.32	927
19.31	671	18.81	762	18.31	825	17.81	874	17.31	928
19.30	673	18.80	764	18.30	826	17.80	875	17.30	930
19.29	674	18.79	765	18.29	827	17.79	876	17.29	931
19.28	676	18.78	767	18.28	828	17.78	877	17.28	933
19.27	677	18.77	768	18.27	829	17.77	878	17.27	934
19.26	679	18.76	770	18.26	830	17.76	879	17.26	936
19.25	680	18.75	771	18.25	831	17.75	880	17.25	937
19.24	682	18.74	773	18.24	832	17.74	881	17.24	939
19.23	684	18.73	775	18.23	833	17.73	882	17.23	940
19.22	685	18.72	777	18.22	834	17.72	883	17.22	942
19.21	687	18.71	778	18.21	835	17.71	883	17.21	944
19.20	689	18.70	780	18.20	837	17.70	884	17.20	946
19.19	691	18.69	781	18.19	838	17.69	885	17.19	948
19.18	692	18.68	782	18.18	839	17.68	886	17.18	950
19.17	694	18.67	784	18.17	840	17.67	887	17.17	952
19.16	696	18.66	785	18.16	841	17.66	888	17.16	954
19.15	698	18.65	786	18.15	842	17.65	889	17.15	956
19.14	700	18.64	788	18.14	843	17.64	890	17.14	959
19.13	702	18.63	789	18.13	844	17.63	891	17.13	962
19.12	704	18.62	790	18.12	845	17.62	892	17.12	964
19.11	706	18.61	792	18.11	846	17.61	893	17.11	967
19.10	708	18.60	793	18.10	847	17.60	894	17.10	970
19.09	710	18.59	794	18.09	848	17.59	895	17.09	973
19.08	712	18.58	795	18.08	849	17.58	896	17.08	976
19.07	714	18.57	797	18.07	850	17.57	898	17.07	979
19.06	716	18.56	798	18.06	851	17.56	899	17.06	982
19.05	718	18.55	799	18.05	852	17.55	900	17.05	985
19.04	720	18.54	800	18.04	853	17.54	901	17.04	988
19.03	722	18.53	801	18.03	854	17.53	902	17.03	991
19.02	724	18.52	802	18.02	854	17.52	903		
19.01	726	18.51	804	18.01	855	17.51	905	17.02	994
19.00	728	18.50	805	18.00	856	17.50	906	17.01	997
18.99	730	18.49	806	17.99	857	17.49	907	17.00	999
18.98	732	18.48	807	17.98	858	17.48	908	16.99	1001

产品规格: Φ _o 20 × Φ _i 10 × h 7mm, 绿色 (Green)	检验工程师 (Inspector): 黄满连
生产批号 (Batch No.): AQS 19	生产日期 (Date): 2012-02-08

ISO 9001:2000

